

Signatone

	PSI Model	Comments / Variations
SE-SM	407F	Signatone shank 2" long. PSI shank 1 1/4" long
SE-SMS	407F/S style	Sharp 7F probe tip.
SM-10	407X	
SM-35	407A	
SE-20T	407B-2	
SE-20TZ	407B2-45-LONG 407B2-60-LONG	
SE-20TB	407B-10	
SE-TG	407B-10G	
SE-TC	407D-3/4	

American Probe and Technologies

	PSI Model	Comments / Variations	
72S-D3/035	407A		
72A-C4/05	407A/05	407A probe with 0.5 um R point	
72T-H3/06	407B		
72T-G4/10	407B-1		
72T-F4/12	407B-2		
72T-J3/70	407B-5		
72C-D/035	407C		
72C-C/05	407C/05		7C probe with 0.5 um R point
72D-E/50	407D		
72D-E3/50	407D-3/4		
72F-B/05	407F		
72G	407B-5G	APT gold plated probes ranging from 2.5 to 25 um R Use either PSI 7B-xxG or 7G-xxG gold plated probe series for point ranges (xx) from 5.0 to 200 um R.	
72X-G3/01	407X		
73 FPC-6000	44-FPCB-V-NA 44-FPCB-S-NA	APT uses SMC type connectors PSI uses either UMC or SMA type	
74CJ-APT-KS/50	44-FPCB-J-NA	APT uses SMC type connectors PSI uses UMC type connectors	

Cascade/Alessi

	PSI Model	Comments / Variations
CW-100	407B-2	
PTT-12	SPP20010601-A	7B-2 long taper without bend
PTT-120/4	SPP20010601-A	7B-2 long taper with bend

GGB / PicoProbe

PSI Model		Comments / Variations
PP12C-1-10	MM-12C-1-10	
PP12C-1-22	MM-12C-1-22	
PP12C-4-10	MM-12C-4-10	
PP12C-4-22	MM-12C-4-22	

Micromanipulator

When specifying any Model 7(n) series probe tip add the prefix 40 to the part number to order from PSI.
[Where (n) = the letter 'A' thru 'X'

Note: Please contact the factory for your needs if you don't see it here.